

TECHNICAL DATA SHEET

| | |
|---------------------------|--|
| TYPE | DUCOGRILLE CLASSIC G 130HP |
| DESCRIPTION | Louvre "build-in" wall grille, high water resistance, high airflow |
| SHAPE OF BLADE | 130HP |
| VISUAL FREE AREA | 88% |
| PHYSICAL FREE AREA | 70% |
| PITCH | 50 mm |
| DEPTH TO FIT | 158 mm |
| FLANGE | 48 mm |
| MINIMUM DIMENSIONS | Width: 250mm Height: 250mm |
| MESH | - standard insect mesh 2,3 x 2,3 SS - optional with mesh 6 x 6 mm - optional with mesh 20 x 20 mm |
| DRIP TRAY PROFILE | Integrated in the frameprofile |
| MATERIALS | Aluminium : AlMg 0,7Si Profile thickness : min. 1,5mm Plastic parts: clips polyamide PA 6.6 - reinforced with glass fibre |
| SURFACE TREATMENT | - anodized according QUALANOD - enamelled polyester powder coating according QUALICOAT |

| K-factor | |
|----------|-------|
| Intake | 8,55 |
| Ce: | 0,34 |
| Exhaust | 13,42 |
| Cd: | 0,27 |

| Water resistance | |
|------------------|-------|
| BSRIA (EN13030) | |
| v (m/s) | class |
| 0 | A |
| 0,5 | A |
| 1 | A |
| 1,5 | A |
| 2 | A |
| 2,5 | A |

