

TECHNICAL DATA SHEET

TYPE	DUCOGRILLE CLASSIC G 45HP
DESCRIPTION	Louvre "build-in" wall grille, high airflow
SHAPE OF BLADE	45HP
VISUAL FREE AREA	70%
PHYSICAL FREE AREA	60%
PITCH	50 mm
DEPTH	62 mm
EQUAL LEG OUTER FRAME	48 mm
MESH	<ul style="list-style-type: none"> - standard with insect mesh 2,3 x 2,3 mm - optionally without mesh - optionally with bird mesh 6 x 6 mm - optionally with bird mesh 20 x 20 mm
MATERIAL	Aluminium : AlMg 0,7Si Profile thickness : min. 1,5mm Thermoplastic parts: clips Polyamide PA 6,6 -reinforced with glass fibre
SURFACE TREATMENT	<ul style="list-style-type: none"> - standard aluminium anodised (15-20µm) - polyester powder coated (60-80µm) - specific RAL colour and/or texture op demand

K-factor	
Intake:	12,66
Ce:	0,281
Exhaust:	6,68
Cd:	0,387

Water resistance	
BSRIA (EN13030)	
v (m/s)	class
0	B
0,5	B
1	C
1,5	C
2	C
2,5	D

